

Accuit Sign[™] 8 PATIENT MONITOR

High Technology & Easy User Interface

A Partner in Health · Investing for Growth

ECG

- Lead type: 5-lead
- Input: RA; LA; RL; LL; V
- Sweep speed: 12.5mm/s, 25mm/s, 50mm/s
- Accuracy: ± 1 bpm or $\pm 1\%$, which is greater
- Protection: Withstand 4000VAC/50Hz voltage in isolation against electro-surgical and defibrillation
- S-T detection: YES, Arrhythmia analysis: YES
- Alarm: YES, audible and visual alarm, alarm events recallable

Standard Configuration

- ECG, NIBP, SPO2
- 12.1" color TFT display
- Suitable for adult, pediatric and neonatal patient
- Basic parameters (ECG, SPO2, NIBP) in a durable case for bedside monitoring and transport monitoring
- Audible and visual alarms with adjustable alarm ranges
- Networkable with central monitoring system
- Powerful data management and storage capacity

NIBP

- Method: Oscillometry
- Operation modes: Manual/Automatic/STAT
- Measurement unit: mmHg/KPa selectable
- Measurement types: Systolic, Diastolic, Mean
- Over-pressure protection: YES

SPO2

- Measurement range: 0-100%
- Accuracy: ± 2 digit (70~100%);
- 0~69% unspecified


Optional

- RESP, 2-TEMP, 2-IBP, ETCO2, Network, Thermal Printer, Pace Maker

Option



EtCO2 MODULE (Side stream)



IBP MODULE



EtCO2 Sampling Cube



IBP Transducer



PRINTER



IBP Cable



Corporate Office

MDXUSA Medical Equipment Solutions **MDX** Instruments

Address: No.2 Central Avenue, Bridgeport, Connecticut, U.S.A 6605
 Homepage: www.mdxinstruments.com E-mail: info@mdxinstruments.com

MDX Instruments reserves the right to make changes; including change in price, content, description, terms, appearance etc. at any time without prior notice.